PPI Liverpool Cancer Centre Schedule of external materials



JDDK Job.No. 3746

Issue date 05th July 2016

Project PPI Liverpool Cancer Centre

Subject Schedule of materials

Planning	Description of Material (Supplier/ Product Code)	Colour / Ref		NBS
Facing Brickwork	Wienerberger Ltd Dorton Manor Stock Fine creased light brown stock brick, with occasional setting marks			45-80-50/316
Inset panels	Wienerberger Ltd Sheerwater silver yellow stock Standard: To BS EN 771-1. Brick description: Facing brick.			45-80-50/316
Wall finishes	Kingspan Insulated Panels Micro-Rib KS1000 MR Colour Adventura	Adve	entura 000	
	Kingspan Insulated Panels Micro-Rib KS1000 MR Colour Gooswing Grey	Grey BS 10	60	

Membrane roof – flat

Reinforced bitumen membrane warm roof covering system

panels/micro-rib/

http://www.kingspanpanels.co.uk/p anels/products/insulated-wallpanels/architectural-wall-

Bauder Ltd – Bauder Total Roof System. Bauder K5K, 5 mm thick, 250g/m² polyester reinforced, elastomeric bitumen torch applied capping sheet, charcoal grey finish. Designated areas of maintenance access walkway defined using Bauder K5K capping sheet, Brown finish.





20-50-30/185 45-65-50/301 (A) 45-65-50/301 (B)

PPI Liverpool Cancer Centre Schedule of external materials



Rainwater Gutters Alumasc Exterior Building Products Ltd

EHR15 Aqualine extruded aluminium

150 mm Half Round gutter

Rainwater Alumasc Exterior Building Products Ltd downpipes

CP40 Flushjoint extruded aluminium

100 mm round pipework

PPC RAL: 7031

90-05-35/320

PPC RAL: 7031

90-10-20/306

Rationel Windows / Doors

Manufacturer:

Rationel Windows (Uk) Ltd 7 Avonbury Business Park

Howes Lane Biceste Oxon OX26 2UA

- Tel: 01869 248181 - Fax: 01869 249693

Web: http://www.rationel.com Product reference: AURAPLUS

Window Materials:

Exterior frame/sash cladding: Frames and sashes to be externally clad with pre-assembled aluminium sections held clear of the timber surface to allow drainage and ventilation.

Finish: Powder coated according to RAL: 7031 to gloss level 77%.

Glazing details: 32mm double glazed units (6mm energy laminated glass to the inside, 22mm air gap, 4mm toughened glass to the outside(w.Argon)). Note - Although generally through out, check window schedules and drawings for conformation.

Door Materials: Exterior frame/door leaf cladding:

Frames and sashes to be

External Frames RAL: 7031 to gloss level

77%.

25-50-95/125 25-50-20/120



PPI Liverpool Cancer Centre Schedule of external materials



externally clad with preassembled aluminium sections held clear of the timber surface to allow drainage and ventilation.

Finish: Powder coated according to RAL No – Colour 7031 to gloss level 77%.

Curtain Wall frame & doors System Supplier: Senior Architectural Systems Ltd (or equal approved) Hybrid Series 3 Composite Curtain Wall System

The finish to all aluminium profiles shall generally be Polyester Powder Coated to BS EN 12206 in a standard RAL colour to satisfy a corrosion classification as defined by the powder manufacturer. Powder coat shall be applied to an average thickness of 60 microns Product Reference: System - Capped Curtain Walling nominal 50mm width for all transoms and mullions Clear double glazing generally; isolated enamelled glass shadowbox spandrel panels RAL7031 to conceal structure.

Internal & External Frames

RAL: 7031 to gloss level 77%.
To match velfac windows & doors

25-80-15/175

External landscaping /hard surfaces

See Oobe Hard landscaping plan