5898 LMH : Standard Details Supplementary Information - Glenacres

| DRAWING | ITEM | NBS | COLOUR | FINISH | MANUFACTURER / TYPE |
|----------|---|---------------------------------|--------------------|--|----------------------------|
| DT(90)00 | CONCRETE FLAG PAVING FOR PATHS AND PEDESTRIAN AREAS | Q25/120 : Q25/315 | Natural | Exposed aggregate | Marshalls Saxon or similar |
| | CONCRETE FLAG PAVING FOR MOWING TRIM ADJACENT BUILDINGS/WALLS | Q25/120A : Q25 315A | Natural | Coarse textured | Marshalls or similar |
| DT(90)01 | PRECAST CONCRETE HALF BATTER KERB | Q10/112A | Grey | As cast | Marshalls or similar |
| DT(90)02 | PRECAST CONCRETE FLUSH EDGING | Q10/113A | Grey | As cast | Marshalls or similar |
| | PRECAST CONCRETE UPSTAND EDGING | Q10/113 | Grey | As cast | N/A |
| DT(90)07 | PRECAST PIER CAPPINGS TO 440MM BRICK PIERS | F31/1F | N/A | As existing | |
| | ENGINEERING BRICKWORK TO CONTRASTING BANDS IN WALLS | F10/385 | Red | N/A | |
| | BRICK WORK | F10/110/385 | Clay | N/A | |
| DT(90)21 | TIMBER GATES 1800 MM HEIGHT CLOSE BOARDED FENCING 1800 MM | Q40/570A | N/A | N/A | |
| | HEIGHT TO REAR BOUNDARY FENCE, REAR PARTY FENCE AND FRONT/REAR DIVISION FENCE | Q40/310A | N/A | N/A | |
| DT(90)25 | TIMBER KNEE RAIL | Q50/170 | N/A | N/A | |
| DT(90)30 | PRECAST STEEP ANGLED CONCRETE COPING | F31/1A | N/A | As existing | |
| | BRICK WORK | F10/110/385 | Clay | N/A | |
| | PRECAST HALF-ROUND COPINGS TO EXTERNAL WALLS | F31/1C | N/A | As existing | |
| DT(90)45 | | Q25/31D, F10/385A & Q50/205B | RAL 9005 Jet Black | Hot dip galvanized to BS EN ISO 1461 and powder coated | |