

## 5898 LMH : Standard Details Supplementary Information - Rodick Street

DRAWING	ITEM	NBS	COLOUR	FINISH	MANUFACTURER / TYPE
DT(90)00	CONCRETE FLAG PAVING FOR PATHS AND PEDESTRIAN AREAS	Q25/120 : Q25/315	Natural	Exposed aggregate	Marshalls Saxon or similar
	CONCRETE FLAG PAVING FOR MOWING TRIM ADJACENT BUILDINGS/WALLS	Q25/120A : Q25 315A	Natural	Coarse textured	Marshalls or similar
DT(90)21	TIMBER GATES 1800 MM HEIGHT CLOSE BOARDED FENCING 1800 MM HEIGHT TO REAR BOUNDARY FENCE, REAR PARTY FENCE AND FRONT/REAR DIVISION FENCE	Q40/570A	N/A	N/A	
		Q40/310A	N/A	N/A	
DT(90)30	BRICK WORK	F10/110/385	Clay	N/A	
DT(90)45	STEPS WITH BRICK RISERS & HANDRAIL	Q25/31D, F10/385A & Q50/205B	RAL 9005 Jet Black	Hot dip galvanized to BS EN ISO 1461 and powder coated	
DT(90)70	1800MM HEIGHT TIMBER PANEL FENCE AND SLOTTED CONCRETE POSTS	Q40/310H	N/A	N/A	