


PLAN

## **REFER TO DRAWING OFFICE FOR** MAIN/CONTRASTING BRICK COLOURS.

TITLE		DATE		DRAWN	с л Ц	REVISIONS	А		Rev	Date	Amendment
	GENERAL		SEP.04		SAH				A	25/06/10	Note regards spacing of piers added.
	STANDARD SCREEN WALL DETAIL 2	SCALE	1:20	CHECKED	-	DRAWING NO	).	1			
							·	F2-3			



NOTES:

- 1. MOVEMENT JOINTS AT 12m MAX DIMENSION. 2. MOVEMENT JOINTS AT CHANGES IN HEIGHT. 3. MOVEMENT JOINTS IN SHORT RETURNS LESS

- MOVEMENT JOINTS ADJACENT TO BUILDING.
  MOVEMENT JOINTS ADJACENT TO BUILDING.
  12mm JOINT WIDTH WITHIN AREOFILL EXPANSION MATERIAL AND MASTIC POINTED TO FINISH.

## FOUNDATIONS

600x200mm STRIP FOOTING TO U/S OF 215 THICK WALL TO BE INCREASED LOCALLY AROUND PIERS. DEPTH OF FOUNDATION TO BE DETERMINED BY SITE CONDITIONS.

GROUND WORKS:

THE STANDARD SPECIFICATION RELATES TO SITES WITHOUT THE FOLLOWING CONDITIONS: SHOULD ANY OF THESE CONDITIONS OCCUR, REFERENCE MUST BE MADE TO OBTAIN THE STRUCTURAL ENGINEERS ADVICE.

1. PRESENCE OF TREES EITHER ON OR ADJACENT SITE

- (REFER TO NHBC PRACTISE NOTE 3). 2. PRESENCE OF PONDS &/OR STREAMS. 3. KNOWLEDGE OF, OR DISCOVERY OF TIPPED OR

- WASTE MATERIALS. 4. KNOWLEDGE OF, OR DISCOVERY OF OLD MINE OR QUARRY WORKINGS



Init
SJM