

UTILITY


1.92 x 1.82 =

CLOAKS 1.90 x 1.40

GARAGE

5.71 x 3.00





Clear space required in WC & Bathroom.

Key:-

Number indicates item related to AD-M4(2) Criterion

Extra items required to comply with Approved

Document M4(2) shown in blue

Approved Document M4(2) Criteria

- 1. Principal entrance to have:
- 1.1. 1200 x 1200mm level external landing covered for a minimum width of 900mm and depth of 600mm.
- Lighting on dusk to dawn or PIR sensor.
- Min. clear opening width of 850mm with a 300mm nib on the leading edge, maintained for a minimum distance of 1200mm beyond it.
- 2. All other external doors must comply with paragraph 1.3
- 3. Hall or Landing clear width is 900mm.
- 4. Door clear widths as AD-M4(2) Table 2.1. 300mm nib to all doors within entrance storey.
- 5. Entrance level living space
- 6. In a dwelling with 3 or more bedrooms, the entrance level WC also allows for a potential level access
- 7. Bathroom and WC walls / ducts / boxings can support fixings (e.g. grab rails, seats and other adaptations)
- 8. 850mm (min.) clear width to stairs when measured 450mm above the pitch line (ignoring any newel post).

Front Elevation



The Oxford $M_4(2)$

Heritage Collection "2017 Edition"

EF Series Brick (B1) 1318sqft 122.43m² DATE: November 2019 REV: -

EF_OXFO_M42_DM.2

Drawing Scale 1:100 @ A3

Rear Elevation

Side Elevation

Side Elevation

Ground Floor

LOUNGE

5.00 x 3.29 5

KITCHEN/DINING


6.46 x 3.68

HALL

* - 750 MIN CLEAR WIDTH ^ - 775 MIN CLEAR WIDTH








UTILITY

CLOAKS 1.90 x 1.40

GARAGE

5.71 x 3.00





Approved Document M4(2) Criteria

1. Principal entrance to have:

Key:-

1.1. 1200 x 1200mm level external landing covered for a minimum width of 900mm and depth of 600mm.

Extra items required to comply with Approved


Number indicates item related to AD-M4(2) Criterion

Clear space required in WC & Bathroom.

Document M4(2) shown in blue.

- Lighting on dusk to dawn or PIR sensor.
- Min. clear opening width of 850mm with a 300mm nib on the leading edge, maintained for a minimum distance of 1200mm beyond it.
- 2. All other external doors must comply with paragraph 1.3
- 3. Hall or Landing clear width is 900mm.
- 4. Door clear widths as AD-M4(2) Table 2.1. 300mm nib to all doors within entrance storey.
- 6. In a dwelling with 3 or more bedrooms, the entrance level WC also allows for a potential level access
- 7. Bathroom and WC walls / ducts / boxings can support fixings (e.g. grab rails, seats and other adaptations)
- 8. 850mm (min.) clear width to stairs when measured 450mm above the pitch line (ignoring any newel post).





1318sqft 122.43m² DATE: November 2019

^ - 775 MIN CLEAR WIDTH

* - 750 MIN CLEAR WIDTH

HALL

KITCHEN/DINING

Rear Elevation

Side Elevation

The Oxford M₄(2) Heritage Collection "2017 Edition"

EF Series Render (A1) REV: -

EF_OXFO_M42_DM.2

Drawing Scale 1:100 @ A3



Ground Floor

LOUNGE


5.00 x 3.29

5




Front Elevation


Side Elevation








Side Elevation






Rear Elevation



Side Elevation

Front Elevation



Key:-



Extra items required to comply with Approved Document M4(2) shown in blue.



Clear space required in WC & Bathroom.



Number indicates item related to AD-M4(2) Criterion

Approved Document M4(2) Criteria

- 1. Principal entrance to have
- 1.1. 1200 x 1200mm level external landing covered for a minimum width of 900mm and depth of 600mm.
- 1.2. Lighting on dusk to dawn or PIR sensor.
- Min. clear opening width of 850mm with a 300mm nib on the leading edge, maintained for a minimum distance of 1200mm beyond it.
- 2. All other external doors must comply with paragraph 1.3
- Hall or Landing clear width is 900mm.
- 4. Door clear widths as AD-M4(2) Table 2.1. 300mm nib to all doors within entrance storey.
- 5. Entrance level living space
- 6. In a dwelling with 3 or more bedrooms, the entrance level WC also allows for a potential level access
- 7. Bathroom and WC walls / ducts / boxings can support fixings (e.g. grab rails, seats and other adaptations)
- 8. 850mm (min.) clear width to stairs when measured 450mm above the pitch line (ignoring any newel post).

The Oxford M₄(2) (Cn1)

Heritage Collection "2017 Edition"

EF Series Brick (B1) 1318sqft 122.43m² DATE: November 2019 REV: -

EF_OXFO_M42_DM.2

Drawing Scale 1:100 @ A3



Ground Floor

