

'LIFETIME HOMES' COMPLIANT APARTMENT TYPE

INTERNAL DOORWAYS

TO INCLUDE:

- A MINIMUM CLEAR OPENING WIDTH OF 750MM WHEN THE APPROACH TO THE DOOR IS 'HEAD ON'.
- A 300MM NIB TO THE LEADING EDGE OF THE DOOR, ON THE PULL SIDE.

LIVING/DINING ROOMS

TO INCLUDE:

- A CLEAR TURNING CIRCLE OF 1500MM DIAMETER.
- A CLEAR WIDTH OF 750MM BETWEEN ITEMS OF LOOSE FURNITURE.

KITCHEN

TO INCLUDE:

- A BUILT IN OVEN AT AN ACCESSIBLE HEIGHT BE SIDE A MINIMUM 600MM OF WORK SURFACE.
- A HOB BESIDE A FURTHER MINIMUM 600MM OF WORK SURFACE, AND A SINK/DRAINER.
- A 3600MM LENGTH MEASURED ALONG THE FRONT FACE IN, L SHAPE.
- A CLEAR WIDTH OF 1200MM BETWEEN KITCHEN UNIT FRONTS / APPLIANCE FRONTS AND ANY FIXED OBSTRUCTION OPPOSITE.

BATHROOM

TO INCLUDE:

- AN ACCESSIBLE BATHROOM, PROVIDING EASE OF ACCESS IN ACCORDANCE WITH LIFETIME HOMES SPECIFICATION PROVIDED AT ENTRANCE LEVEL.
- A CLEAR ZONE ALONGSIDE THE BATH, 1100MM LONG AND 700MM WIDE.
- FLOOR DRAIN UNDER BATH TO PROVIDE FUTURE LEVEL SHOWER.
- ABILITY TO ADAPT EXISTING TO CREATE LARGER ACCESSIBLE SHOWER/BATHROOM ACCESSED DIRECTLY FROM MAIN BEDROOM

BEDROOMS

TO INCLUDE:

- 750MM WIDE TO BOTH SIDES AND THE FOOT OF A STANDARD SIZED DOUBLE BED IN MAIN BEDROOM.
- 750MM WIDE, TO ONE SIDE OF THE BED IN THE SMALLER BEDROOM.

POTENTIAL FOR FUTURE FITTING OF HOISTS BETWEEN BEDROOM & BATHROOM

TO INCLUDE:

- STRUCTURE ABOVE A MAIN BEDROOM AND BATH ROOM CEILINGS CAPABLE OF SUPPORTING CEILING HOISTS.
- A FULL HEIGHT 'KNOCK OUT PANEL' SUFFICIENT TO FORM A DIRECT DOORWAY WITH A MINIMUM CLEAR OPENING WIDTH OF 900MM BETWEEN THE TWO ROOMS, OR HAVE A DIRECT (EN-SUITE) LINK WITH A MINIMUM CLEAR DOORWAY OPENING OF 900MM FROM THE OUTSET.



Second Floor Edward Pavilion Albert Dock Liverpool L3 4AF 0151 958 0200 info@blokarchitecture.co

