

Stannah Midilift SL/GL

Standard
platform lifts

The Stannah Midilift standard platform lift range offers a simple, cost effective way to provide access for all within public, commercial or domestic buildings.

www.stannahlifts.co.uk

Stannah

Stannah Midilift standard platform lifts

Introduction



Our latest Midilift standard platform lift combines design versatility and intuitive use with ease of installation and reliable performance - with more finish choices to customise your lift to suit your building and more user-friendly features for the end user.

Midilift standard platform lifts can be installed in new and existing buildings, complementing and blending into any environment, either internally or externally. Predominantly used as wheelchair or disabled lifts, these lifts require no pit, are installed in their own structure and can travel up to 7 metres. The half height gate option, for up to 3m travels, is ideal for enabling access to mezzanine floors or where there are headroom restrictions.

Our platform lifts help building designers and owners to meet the requirements of Part M and BS 8300, as well as helping to meet obligations under EN81-41 and the Equality Act (formerly the DDA), whilst taking up the minimal amount of building space possible.

A UK manufacturer, Stannah have proudly provided more than 4,000 Midilift platform lifts. These lifts are installed throughout the UK, across all market sectors, including education, retail, offices, public buildings and private residences. Our proven hydraulic drive and energy-efficient lighting coupled with our nationwide service ensures our lifts run smoothly and efficiently for years, adding value to any building.



Stannah Midilift standard platform lifts

Products

Products


There are two products in the standard Midilift range -

Midilift SL

The Midilift SL platform lift travels up to 7 metres providing a solution for higher travel and an increased number of stops. There is a wide range of design options for the structure and platform to ensure the lift matches your building requirements.

Midilift GL

The Midilift GL platform lift is a low-cost option for mezzanine floors. This lift travels up to 3 metres with a half height gate at the top. It can also be an ideal solution if headroom is restricted on the second floor.



The option of a ramp where required



The Midilift SL standard platform lift



The Midilift GL with a half height gate at the top – an ideal solution if headroom is restricted on the second floor.

Stannah Midilift standard platform lifts

Key benefits

Key benefits

- Up to 7m travel with three platform sizes available to suit buildings of different shapes and sizes
- Compact shaft with a choice of entrance configurations
- Minimal builders work required and quick installation time
- Structure-supported enclosure – no lifting beam required
- Flexibility on drive control unit location
- Low pit requirements with ramp where a 70mm recess is not possible
- Low running and maintenance costs due to the single phase power consumption
- Choice of finishes or branding to complement any building design and to make your lift unique
- Helps building owners to conform with Part M and the Equality Act

External products are available – please contact us for further information.

BREEAM

By using a Midilift for your project instead of a lift with a speed greater than 0.15m/s the BREEAM criteria does not apply, reducing the overall BREEAM total and whole building project score.

Installation & Warranty

Installation typically 1-4 days, depending on site conditions and lift travel.

All our lifts are supplied with a 12-month warranty with four service visits as standard and we offer a range of service options tailored to suit your specific requirements.

Stannah also offer cabin platform lifts – the Midilift Plus range offering the feel of a passenger lift but with all the access benefits of a platform lift - ask for further details.



Stylish brushed aluminium console

DDU as standard

Mid panel providing visual contrast design

Larger, easy to use buttons

Longer handrail

45° angle for easier operation

Stannah Midilift standard platform lifts

Features and options at a glance

Standard features:

Carriage:

Large illuminated constant pressure call buttons – 50mm square

Audible and visual notification of floor level and travel direction

Voice annunciation with arrival chime

Alarm button

Emergency stop switch

Red digital display units with direction arrow and overload indicator

Battery backed up LED lighting

800mm handrail in satin stainless steel

Mechanical safety edges around platform

Landing features:

Complete lift isolation keyswitch (supplied on lower landing only)

Landing controls:

One-touch landing controls mounted on door frame

Other features:

Emergency lowering of the lift from inside platform in the event of power failure

Two-way intercom communication system for emergency calls

Emergency lighting and alarm with back-up battery

Structure:

Structure supported enclosure with powder coated steel solid infill panels

LED ceiling spot lights with timer (SL only)

Doors:

Panoramic glass door fitted with door opener/closer

800/900mm clear opening at each entrance

† There are instances in which we can reduce the headroom – please contact us to discuss further.



Options available:

Carriage:

Joystick – 2 floor lift only

Landing features:

Keyswitch isolation of call button

Red digital display units with fixed direction arrow

Landing controls:

Remote landing call stations flush or surface mounted

Pedestal mounted landing call stations

Other features:

Battery backup in both directions

Klaxon alarm fitted to structure

Telephone

Memcom auto-dialler/auto-dialler with inductive loop

Volt free alarm contacts

Fire alarm shutdown (to lowest floor only)

Welsh signage and instructions

Structure:

Glass panels

Fixing hoop if required

Fixed ramp

Special fixing brackets if required

Extended enclosure

Pre-drilled full enclosure/landings/sides (fire cladding)

Reduced headroom †

Door options:

30/60 min fire rated door – primed or wood finish (see below)

Doors by others


Half height gate – GL

Automatic door opener/closer


Concealed door closer




Wood finishes for fire door




White Oak



Ash




Red Oak



Beech

Stannah Midilift standard platform lifts


Finishes

	Standard	Options	
Structure, door frame, carriage and platform	White	Light Grey	Dark Grey
Mid panel	Dark Grey	Stainless Steel	Light Grey
Floor	Grey Safety Floor	Vinyl stud Light Grey	Vinyl stud Dark Grey
		Slate effect PVC	Oak effect laminate
		 Flooring by others	
Doors	White	Light Grey	Dark Grey

Colours: White is BS22B15; Light Grey is RAL 7035; Dark Grey is RAL 7016



Bespoke Options

Our bespoke solutions offer you a wide range of RAL colours on all of the above components. Choose from a wide range of alternative finishes to ensure your lift meets your specifications. Colours, glass, flooring and more can be selected from a wide range of materials.



Stannah Midilift standard platform lifts

Technical data



Dimensions

Platform size (w x d)	Footprint size (w x d)	Pit depth	Headroom
950 x 1250	1210 x 1410 [◇]	70*	Variable – please see notes [†]
950 x 1400 [#]	1210 x 1530 [◇]	70*	
1100 x 1400 [‡]	1330 x 1530 [◇]	70*	

Technical specifications

	Midilift GL ½ height gate	Midilift SL Full height door
Standard load	400kg	
Maximum travel	3m	7m
Speed of travel	Up to 0.15m/s	
Drive system	Hydraulic (includes external control unit)	
Platform control system	Constant pressure	
Power supply	240v single phase	

Notes:

All dimensions are in mm

* A ramp can be used where this pit depth is not possible.

† Headroom is dependent upon the travel – please contact us for more information.

Part M (England and Wales) compliant (950 x 1400 for unattended wheelchair use and 1100 x 1400 for attended use).


‡ Section 4.2 (Scotland) compliant.

◇ For aperture, allow +30mm on each dimension over and above the footprint.

The Midilift helps to meet the requirements of:

- The Equality Act
- Part M of the Building Regulations (England and Wales) and Section 4.2 of the Technical Handbook (Scotland), both of which cover the requirements that many new buildings must meet to ensure ease of access and use
- BS8300:2009 Code of Practice covering the design of buildings and their approaches to meet the needs of disabled people

All of our Midilifts are CE marked and comply with the latest Machinery Directive 2006/42/EC.



NBS Specifications, CAD blocks and data sheets giving further technical information are all available from our web site

www.stannahlifts.co.uk/downloads

Stannah knows how to help people get on with their lives. Whether it is a passenger lift at the station, a dumbwaiter at the coffee shop, an escalator in the shopping centre, or a stairlift at home – we are there quietly helping life happen.

With over 140 years of experience and expertise in the lift industry, we offer customers right across the UK a complete range of lifting solutions to move people and goods efficiently, reliably and safely. We are proud of our reputation for outstanding customer service, delivered from our network of branches.

Whatever your lifting requirements, Stannah can provide a solution.



Stannah Lifts

Anton Mill, Andover, Hampshire SP10 2NX

Telephone: 01264 339090

Midiift 02/15

Meet the family



Stairlifts



Passenger Lifts



Escalators and Moving Walkways



Platform Lifts



Service and Goods Lifts



Lift Refurbishment



Bespoke Lifts



Lift Service and Repair